

Principal dimensions				Basic load ratings		Basic load ratings		Limiting Speed		Designation	Distance of action point	Installation dimensions			Weight
外形尺寸				额定载荷		额定载荷		极限转速		轴承代号	作用点距离	安装尺寸 (mm)			重量
d	D	B	r	Cr	Cor	Cr	Cor	(rpm)			a ₀	d _a	Da	r _a	(kg)
			min(最小)	(N)		{kgf}		脂润滑	油润滑		(mm)	min(最小)	max(最大)	max(最大)	
30	62	16	1	31000	45000	3150	4600	8500	12000	QJ206	32.2	36	56	1	0.24
35	72	17	1.1	41000	61500	4200	6250	7500	10000	QJ207	37.5	42	65	1	0.35
40	80	18	1.1	49000	77500	5000	7900	6700	9000	QJ208	42	47	73	1	0.45
45	85	19	1.1	55000	88500	5600	9000	6300	8500	QJ209	45.5	52	78	1	0.52
50	90	20	1.1	57000	97000	5850	9900	5600	8000	QJ210	49	57	83	1	0.59
55	100	21	1.5	71000	122000	7200	12500	5300	7100	QJ211	54.3	64	91	1.5	0.77
60	110	22	1.5	85500	150000	8750	15300	4800	6300	QJ212	59.5	69	101	1.5	0.98
65	120	23	1.5	97500	179000	9950	18300	4300	6000	QJ213	64.8	74	111	1.5	1.2
70	125	24	1.5	106000	197000	10800	20100	4000	5600	QJ214	68.3	79	116	1.5	1.3
75	130	25	1.5	110000	212000	11200	21700	3800	5300	QJ215	71.8	84	121	1.5	1.5
80	140	26	2	124000	236000	12600	24100	3600	5000	QJ216	77	90	130	2	1.85
85	150	28	2	143000	276000	14600	28200	3400	4800	QJ217	82.3	95	140	2	2.2
90	160	30	2	164000	320000	16700	32500	3200	4300	QJ218	87.5	100	150	2	2.75
95	170	32	2.1	177000	340000	18000	35000	3000	4000	QJ219	92.8	107	158	2	3.35