

Principal dimensions				Basic load ratings		Basic load ratings		Limiting Speed		Designation	Distance of action point	Installation dimensions			Weight
外形尺寸				额定载荷		额定载荷		极限转速		轴承代号	作用点距离	安装尺寸 (mm)			重量
d	D	B	r	Cr	Cor	Cr	Cor	(rpm)			a ₀	d _a	Da	r _a	(kg)
			min(最小)	(N)		{kgf}		脂润滑	油润滑		(mm)	min(最小)	max(最大)	max(最大)	
15	42	19	1	17600	10200	1800	1040	11000	15000	5302	22	21	36	1	0.11
17	47	22.2	1	21000	12600	2140	1280	10000	13000	5303	25	23	41	1	0.14
20	52	22.2	1.1	24600	15000	2510	1530	9000	12000	5304	26.7	27	45	1	0.23
25	62	25.4	1.1	32500	20700	3350	2110	7500	10000	5305	31.8	32	55	1	0.34
30	72	30.2	1.1	40500	28100	4150	2870	6300	8500	5306	36.5	37	65	1	0.51
35	80	34.9	1.5	51000	36000	5200	3700	5600	7500	5307	41.6	44	71	1.5	0.79
40	90	36.5	1.5	56500	41000	5800	4200	5300	6700	5308	45.5	49	81	1.5	1.05
45	100	39.7	1.5	68500	51000	7000	5200	4500	6000	5309	50.6	54	91	1.5	1.4
50	110	44.4	2	81500	61500	8300	6250	4300	5600	5310	55.6	60	100	2	1.95
55	120	49.2	2	95000	73000	9700	7450	3800	5000	5311	60.6	65	110	2	2.3
60	130	54	2.1	125000	98500	12800	10000	3400	4500	5312	69.2	72	118	2	3.15
65	140	58.7	2.1	142000	113000	14500	11500	3200	4300	5313	72.8	77	128	2	3.85
70	150	63.5	2.1	159000	128000	16200	13100	3000	3800	5314	78.3	82	138	2	4.9