

Part No.	Shaft Size d		Dimensions (mm) (in)						Basic Load Rating (CN)	Basic Static Load Rating (Co N)	Max rpm	Weight
型号	轴径		尺寸						基本额定载荷	基本额定静载荷	最大转速	重量
	mm	in	A	B	C	D	J	W	lbf	lbf		kg
SUC204-20MM	20		18.3	12.7	28.5	47	31	17	10560	5190	7450	0.2
SUC201-8		1/2	0.72	0.5	1.12	1.8504	1.22	0.669	2400	1180	7450	0.2
SUC202-10		5/8									7450	0.2
SUC204-12		3/4									7450	0.2
SUC205-25MM	25		19.8	14.3	34	52	34.1	17	11440	6290	6250	0.2
SUC205-14		7/8	0.78	0.56	1.34	2.0472	1.34	0.669	2600	1430	6250	0.2
SUC205-15		15/16									6250	0.2
SUC205-16	1	1									6250	0.2
SUC206-30MM	30		22.2	15.9	40	62	38.1	19	16280	8900	5300	0.3
SUC206-18		1-1/8	0.87	0.63	1.57	2.4409	1.5	0.748	3700	2030	5300	0.3
SUC206-19		1-3/16									5300	0.3
SUC206-20		1-1/4									5300	0.3
SUC207-35MM	35		25.4	17.5	46.7	72	42.9	20	21340	12320	4500	0.5
SUC207-20		1-1/4	1	0.69	1.84	2.8346	1.69	0.787	4850	2800	4500	0.5
SUC207-22		1-3/8									4500	0.5
SUC207-23		1-7/16									4500	0.5
SUC208-40MM	40		30.2	19	52.7	80	49.2	21	24640	14080	4000	0.7
SUC208-24		1-1/2	1.19	0.75	2.07	3.1496	1.94	0.827	5600	3200	4000	0.7
SUC209-45MM	45		30.2	19	57.3	85	49.2	22	27280	15840	3700	0.7
SUC209-27		1-11/16	1.19	0.75	2.26	3.3465	1.94	0.866	6200	3600	3700	0.7
SUC209-28		1-3/4									3700	0.7
SUC210-50MM	50		32.6	19	62.2	90	51.6	24	29920	18500	3400	0.8
SUC210-31		1-15/16	1.28	0.75	2.45	3.5433	2.03	0.945	6800	4200	3400	0.8
SUC210-32		2									3400	0.8
SUC211-55MM	55		33.4	22.2	68.8	100	55.6	25	32560	24640	3100	1.1
SUC211-32		2	1.31	0.87	2.71	3.93	2.19	0.984	7400	5600	3100	1.1
SUC211-35		2-3/16									3100	1.1
SUC212-60MM	60		39.7	25.4	75.4	110	65.1	27	39600	30360	2800	1.5
SUC212-39		2-7/16	1.56	1	2.97	4.3307	2.56	1.063	9000	6900	2800	1.5
SUC215-47	—	2-15/16	1.75	1.31	3.62	5.1181	3.06	1.26	48400	40700	2300	2.2
SUC215-48	—	3	11000	9250							2300	2.2